


K2-1.37III Series for 2.54mm [100mil] Pitch

K2-1.37III Series Plunger Tip Styles


Unit: mm [inch]

Probe Length: 32.9mm [1.295inch]



■ スプリングプローブ仕様 Spring Probe Specifications

推奨ストローク Operating Travel	4.27mm [0.168 inch]
荷重 Spring Force at Operating Travel	165gf [5.82oz.]
初期荷重 Initial Force	58gf [2.05oz.]
最大ストローク Max Travel	6.4mm [0.252 inch]
スプリング耐久回数 Life Span at Operating Travel	100万回 (1,000K Cycles)
抵抗値 Resistance (Typ.)	35mΩ
最大許容電流値 Current Rating (Typ.)	5.4A
使用温度 Operating Temp.	-45°C ~ 125°C
Material/Finish	
Plunger	BeCu / Au
Barrel	Nickel Silver / Au
Spring	Music Wire / Au
Ball	Brass / Au



■ リセプタクル品名 Receptacle

K2-1.37S-29.2L-SP24.6

(末端加工無し / No Termination)



K2-1.37S-29.2L-SP24.6-U

(ソルダーカップ付 / with Solder Cup)



K2-1.37-III-S-1

(末端加工無し / No Termination)



K2-1.37-III-S-1-U

(ソルダーカップ付 / with Solder Cup)



■ リセプタクル仕様 Receptacle Specifications

K2-1.37S-29.2L-SP24.6 / K2-1.37S-29.2L-SP24.6-U	
Material/Finish	Brass / Au
K2-1.37-III-S-1 / K2-1.37-III-S-1-U	
Material/Finish	Nickel Silver / Au


Standard Type

K2-1.37III Series for 2.54mm [100mil] Pitch


K2-1.37III Series Plunger Tip Styles

Unit: mm [inch]


Probe Length: 35.9mm [1.413inch]



K2-1.37III-K-11.4M1.5-3



K2-1.37III-O-11.4M1.4-4



スプリングプローブ仕様 Spring Probe Specifications

K2-1.37III-K-11.4M1.5-3

推奨ストローク Operating Travel	4.27mm [0.168 inch]
荷重 Spring Force at Operating Travel	165gf [5.82oz.]
初期荷重 Initial Force	58gf [2.05oz.]
最大ストローク Max Travel	6.4mm [0.252 inch]
スプリング耐久回数 Life Span at Operating Travel	100 万回 (1,000K Cycles)
抵抗値 Resistance (Typ.)	35mΩ
最大許容電流値 Current Rating (Typ.)	7.0A
使用温度 Operating Temp.	-45°C~125°C

Material/Finish

Plunger	BeCu / Au
Barrel	Nickel Silver / Au
Spring	Music Wire / Au
Ball	Brass / Au

K2-1.37III-O-11.4M1.4-4

推奨ストローク Operating Travel	4.27mm [0.168 inch]
荷重 Spring Force at Operating Travel	157gf [5.54oz.]
初期荷重 Initial Force	50gf [1.76oz.]
最大ストローク Max Travel	6.4mm [0.252 inch]
スプリング耐久回数 Life Span at Operating Travel	100 万回 (1,000K Cycles)
抵抗値 Resistance (Typ.)	35mΩ
最大許容電流値 Current Rating (Typ.)	6.7A
使用温度 Operating Temp.	-45°C~125°C

Material/Finish

Plunger Needle	Music Wire / Ni
Shaft - Needle Holder	SK (Steel) / Ni
Barrel	Nickel Silver / Au
Spring	Music Wire / Au
Ball	Brass / Au

リセプタクル 品名 Receptacle

K2-1.37S-29.2L-SP24.6

(末端加工無し / No Termination)



K2-1.37S-29.2L-SP24.6-U

(ソルダーカップ付 / with Solder Cup)



K2-1.37-III-S-1

(末端加工無し / No Termination)



K2-1.37-III-S-1-U

(ソルダーカップ付 / with Solder Cup)



リセプタクル仕様 Receptacle Specifications

K2-1.37S-29.2L-SP24.6 / K2-1.37S-29.2L-SP24.6-U

Material/Finish	Brass / Au
-----------------	------------

K2-1.37-III-S-1 / K2-1.37-III-S-1-U

Material/Finish	Nickel Silver / Au
-----------------	--------------------